

**COUPLING FORGE**

Forged fittings ASTM A105 3000 lb / 6000 lb.

A coupling is used as a connecting joint between pipes and fittings with either threaded (NPT) or socket weld ends. A half coupling is generally used for branching or vessel connections. It can have BSP threaded, screwed or socket weld ends. A full coupling is generally used for connecting pipes or items with either threaded or socket ends.

**3000 lbs sizes available**

Size (mm)	6	8	10	15	20	25	32	40	50	65	80
Available ends	Screwed full	Screwed full	Screwed full	Screwed full	Screwed full	Screwed full	Screwed full	Screwed full	Screwed full	Screwed full	Screwed full
		Screwed half	Screwed half	Screwed half	Screwed half	Screwed half	Screwed half	Screwed half	Screwed half		Screwed half
		Socket weld full	Socket weld full	Socket weld full	Socket weld full	Socket weld full	Socket weld full	Socket weld full	Socket weld full		
		Socket weld half		Socket weld half	Socket weld half	Socket weld half	Socket weld half	Socket weld half	Socket weld half		
				BSP full							

**6000 lbs sizes available**

Size (mm)	15	20	25	50
Available ends	Screwed full		Screwed full	
	Screwed half			
	Socket weld full			Socket weld full
	Socket weld half	Socket weld half	Socket weld half	